

# KGM03AR71A151KH Datasheet

(0201 10 V X7R 150pF  $\pm 10\%$ )

To download data and simulation models visit: **SpiCAT** ONLINE TOOL



## Dimensions




	millimetres	inches
L	0.6 $\pm$ 0.03	0.024 $\pm$ 0.001
W	0.3 $\pm$ 0.03	0.012 $\pm$ 0.001
T max.	0.33	0.013
t	0.15 $\pm$ 0.05	0.006 $\pm$ 0.002


## Basic Specifications

Item	Unit	Spec.	Conditions
Capacitance	pF	135 to 165	@ 1 kHz, 1 Vrms
DF	%	12.5 max.	@ 1 kHz, 1 Vrms
IR	G $\Omega$	100 min.	@ 10 Vdc, t = 120 s
DWV	Vdc	25	@ I $\leq$ 50mA, t $\leq$ 5 s
Operating Temperature		-55°C to +125°C	
Dielectric		X7R	
Product Level		General	
RoHS Compliant		Yes	
Termination		Sn	

## Electrical Characteristics



## Electrical Characteristics



# KGM03AR71A151KH Datasheet



(0201 10 V X7R 150pF ±10%)

## Part Number Information

K	G	M	21	C	R5	1E	103	K	T	###
Symbol:	Product Level:	Requirement:	Size:	Thickness:	Dielectric:	Voltage:	Capacitance:	Tolerance:	Packing:	Optional:
KAVX	G General	M Standard	Code: EIA:	See catalog	CG C0G	Multiplier: Base:	(2 significant digits	A ± 0.05 pF	H	See catalog for optional codes
	A Automotive	U Hi-Q (Special function)	02 01005	for list of codes	R5 X5R	0 1x A 1	+ no of zeros)	B ± 0.1 pF	T	
	(AEC-Q200)	E ESD (Special function)	03 0201		S6 X6S	1 10x N 1.5		C ± 0.25 pF	U	Φ 180 (7 inch)*
	M Medical	L Low inductance reverse Geometry	05 0402	T6 X6T	2 100x D 2		Examples:	D ± 0.5 pF	Y	
		A Low Inductance LGA	15 0603	R7 X7R	3 1000x E 2.5		100 = 10 pF	F ± 1 %	V	
		F Flexitem (Special function/structure)	21 0805	S7 X7S	U 3		102 = 1000 pF	G ± 2 %		
		S Flexisafe (Special function/structure)	31 1206	T7 X7T	V 3.5		224 = 220 nF	J ± 5 %	M	
		G Gold Termination (Special Structure)	32 1210	R8 X8R	G 4		105 = 1 μF	K ± 10 %	L	
		C IDC (Special structure)	42 1808	L8 X8L	H 5			M ± 20 %	N	Φ 330 (13 inch)*
		Q Ultra Low ESR	43 1812	G8 X8G	J 6.3				K	
			44 1825	V5 Y5V					S	
			55 2220			Example:				
			56 2225			1E = 25V (10 x 2.5)			X	Waffle pack
			91 3640							
<b>Note:</b>										
* See catalog for more information.										

**NOTICE:** Specifications are subject to change without notice. All statements, information and data given herein are believed to be accurate and reliable, but are presented without guarantee or responsibility of any kind, expressed or implied. Specifications are typical and may not apply to all applications.