

# VC120665M131RP

(1206, 65Vdc, 1J, 150A, 250pF, Sn Term)

Multilayer Chip Varistor Datasheet

## BASIC SPECIFICATION


Case Size [EIA]	1206
Operating Temperature	-55 to +125°C
Grade	General
Termination	Sn
RoHS	Yes
MSL Level	1
Packaging	T&R 7in (180mm)
Packaging Qty	2000 pcs



## ELECTRICAL CHARACTERISTICS

DC Working Voltage	65 Vdc
AC Working Voltage	50 Vac
Breakdown Voltage [1mA DC]	82.0±10% V
Clamping Voltage [8x20µs]	135V @ 1A
Max Leakage Current [Vdc, 25°C]	15 µA
Transient Energy [10x1000µs]	1 J
Peak Power [10x1000µs]	750 W
Peak Current Rating [8x20µs]	150 A
Typical Capacitance [1kHz, 0.5Vrms, 25°C]	250 pF
Capacitance Tolerance	+100/-50%

## DIMENSIONS



	mm	inches
L	3.20±0.20	0.126±0.008
W	1.60±0.20	0.063±0.008
T	1.8 max	0.071 max
t	0.94 max	0.037 max

## SOLDERING PAD



	mm	inches
A	1.02	0.04
B	2.03	0.08
C	4.06	0.16
D	1.65	0.065

## HOW TO ORDER

<b>VC</b>	<b>1206</b>	<b>65</b>	<b>M</b>	<b>131</b>	<b>R</b>	<b>P</b>
Varistor Chip	Case Size	Working Voltage	Energy Rating	Clamping Voltage	Packaging	Termination
		65 = 65Vdc	M = 1J	131 = 135V	D = 7" reel (1,000pcs) R = 7" reel (2,000pcs) T = 13" reel (10,000pcs)	P = Sn


# VC120665M131RP

(1206, 65Vdc, 1J, 150A, 250pF, Sn Term)


Multilayer Chip Varistor Datasheet

## TYPICAL CHARACTERISTICS


Temperature Derating (Energy, Current, Power)



Power Derating



Voltage / Current



S21

