

## NTC SMD Thermistor with AgPdPt termination

for Automotive, Industrial and General applications

To view data online visit:

**SpiCAT**



KYOCERA AVX Chip NTC Thermistors are high quality devices developed especially for surface mounting applications. They are widely used for temperature compensation, but can also achieve temperature control of printed circuits in a wide range of applications, including automotive, industrial and general purpose. AgPdPt termination termination for conductive adhesive assembly (not suitable for lead free soldering - use NB series).

## Characteristics

Case Size	0805
Operating temperature	-55°C to +150°C
Resistance	39 kOhm
Tolerance on Resistance (25°C)	$\pm 5\%$
B 25/85	3950K $\pm 3\%$
Maximum dissipation at 25°C	0.12 W
Thermal dissipation factor	2 mW/°C
Thermal time constant	5 s
Termination	AgPdPt (for conductive adhesive)



MSL 1



**AEC-Q200**  
based qualification

## Dimensions

mm (inches)

Size (EIA)	Length (L)	Width (W)	Thickness (T)	Terminal (t)
0805	2.0 $\pm 0.3$	1.25 $\pm 0.2$	1.3 max	0.2 min
	(0.079 $\pm 0.012$ )	(0.049 $\pm 0.008$ )	(0.051) max	(0.008) min



## How to Order (Packaging options)

<b>NC</b>	<b>12</b>	<b>M0</b>	<b>0393</b>	<b>J</b>	<b>BB</b>
Type	Size	Material Code	Resistance (Ohm)	Tolerance	Suffix: Packaging
NC = AgPdPt for conductive adhesive	12 = 0805	See Datasheet	2 Sig. Digits + Number of Zeros	H = $\pm 3\%*$ J = $\pm 5\%$ K = $\pm 10\%$ M = $\pm 20\%$	BB = Cardboard tape (180mm reel, 4,000 pcs/reel) BF = Cardboard tape (180mm reel, 2,000 pcs/reel) BD = Cardboard tape (330mm reel, 10,000 pcs/reel) -- = Bulk (5000 pcs/bag)

\* For selected PNs

NOTICE: Specifications are subject to change without notice. All statements, information and data given herein are believed to be accurate and reliable, but are presented without guarantee or responsibility of any kind, expressed or implied. Specifications are typical and may not apply to all applications.

## Material Table

**M0 (B25/85 = 3950K $\pm 3\%$ )**

T (°C)	R(T) / R25	TF (%)	$\alpha$ (%/°C)
-55	99.59	15.64	-7.42
-50	68.97	14.25	-7.16
-45	48.40	12.94	-6.91
-40	34.38	11.69	-6.67
-35	24.71	10.51	-6.45
-30	17.97	9.39	-6.23
-25	13.20	8.33	-6.02
-20	9.804	7.31	-5.82
-15	7.352	6.35	-5.63
-10	5.565	5.43	-5.45
-5	4.251	4.55	-5.28
0	3.275	3.70	-5.11
5	2.544	2.90	-4.95
10	1.992	2.13	-4.80
15	1.572	1.39	-4.65
20	1.249	0.68	-4.51
25	1.000	0.00	-4.38
30	0.8057	0.66	-4.25
35	0.6534	1.30	-4.12
40	0.5331	1.92	-4.00
45	0.4376	2.53	-3.89
50	0.3612	3.12	-3.77
55	0.2998	3.70	-3.67
60	0.2501	4.26	-3.57
65	0.2097	4.81	-3.47
70	0.1767	5.35	-3.37
75	0.1496	5.87	-3.28
80	0.1272	6.38	-3.19
85	0.1087	6.88	-3.11
90	0.0932	7.37	-3.03
95	0.0803	7.84	-2.95
100	0.0694	8.31	-2.87
105	0.0602	8.76	-2.80
110	0.0524	9.21	-2.73
115	0.0458	9.64	-2.66
120	0.0402	10.07	-2.60
125	0.0353	10.48	-2.53
130	0.0312	10.89	-2.47
135	0.0276	11.29	-2.41
140	0.0245	11.68	-2.36
145	0.0218	12.06	-2.30
150	0.0194	12.43	-2.25

B25/50	B25/75	B25/85	B25/100	B Tol
3925 K	3944 K	3950 K	3958 K	$\pm 3\%$

R Min (Ω)	R Nom (Ω)	R Max (Ω)
3,082,442	3,884,018	4,685,594
2,172,159	2,690,002	3,207,846
1,548,842	1,887,409	2,225,975
1,116,953	1,340,794	1,564,635
814,283	963,820	1,113,357
599,843	700,707	801,570
446,310	514,948	583,586
335,272	382,358	429,445
254,184	286,722	319,259
194,414	217,043	239,673
149,962	165,788	181,613
116,617	127,735	138,853
91,396	99,234	107,072
72,167	77,705	83,244
57,394	61,311	65,228
45,961	48,729	51,497
37,050	39,000	40,950
29,645	31,423	33,201
23,877	25,481	27,086
19,352	20,791	22,230
15,780	17,065	18,349
12,942	14,086	15,230
10,674	11,691	12,708
8,850.6	9,754.1	10,658
7,376.8	8,179.4	8,982.0
6,179.1	6,892.3	7,605.5
5,200.6	5,834.9	6,469.2
4,397.3	4,962.0	5,526.8
3,734.5	4,238.0	4,741.5
3,185.2	3,634.7	4,084.3
2,727.9	3,129.9	3,531.9
2,345.6	2,705.6	3,065.7
2,024.5	2,347.6	2,670.7
1,753.9	2,044.3	2,334.7
1,524.8	1,786.4	2,047.9
1,330.3	1,566.2	1,802.2
1,164.4	1,377.6	1,590.9
1,022.4	1,215.5	1,408.7
900.6	1,075.8	1,251.0
795.6	954.8	1,114.1
704.9	849.9	994.9
626.3	758.5	890.8