

## NTC SMD Thermistor with AgPdPt termination

for Automotive, Industrial and General applications

To view data online visit:

**SpiCAT**



KYOCERA AVX Chip NTC Thermistors are high quality devices developed especially for surface mounting applications. They are widely used for temperature compensation, but can also achieve temperature control of printed circuits in a wide range of applications, including automotive, industrial and general purpose. AgPdPt termination termination for conductive adhesive assembly (not suitable for lead free soldering - use NB series).

## Characteristics

Case Size	0805
Operating temperature	-55°C to +150°C
Resistance	39 kOhm
Tolerance on Resistance (25°C)	$\pm 20\%$
B 25/85	3950K $\pm 3\%$
Maximum dissipation at 25°C	0.12 W
Thermal dissipation factor	2 mW/°C
Thermal time constant	5 s
Termination	AgPdPt (for conductive adhesive)



MSL 1



**AEC-Q200**  
based qualification

## Dimensions

mm (inches)

Size (EIA)	Length (L)	Width (W)	Thickness (T)	Terminal (t)
0805	2.0 $\pm 0.3$	1.25 $\pm 0.2$	1.3 max	0.2 min
	(0.079 $\pm 0.012$ )	(0.049 $\pm 0.008$ )	(0.051) max	(0.008) min



## How to Order (Packaging options)

<b>NC</b>	<b>12</b>	<b>M0</b>	<b>0393</b>	<b>M</b>	<b>BF</b>
Type	Size	Material Code	Resistance (Ohm)	Tolerance	Suffix: Packaging
NC = AgPdPt for conductive adhesive	12 = 0805	See Datasheet	2 Sig. Digits + Number of Zeros	H = $\pm 3\%*$ J = $\pm 5\%$ K = $\pm 10\%$ M = $\pm 20\%$	BB = Cardboard tape (180mm reel, 4,000 pcs/reel) BF = Cardboard tape (180mm reel, 2,000 pcs/reel) BD = Cardboard tape (330mm reel, 10,000 pcs/reel) -- = Bulk (5000 pcs/bag)

\* For selected PNs

NOTICE: Specifications are subject to change without notice. All statements, information and data given herein are believed to be accurate and reliable, but are presented without guarantee or responsibility of any kind, expressed or implied. Specifications are typical and may not apply to all applications.

## Material Table

**M0 (B25/85 = 3950K $\pm 3\%$ )**

T (°C)	R(T) / R25	TF (%)	$\alpha$ (%/°C)
-55	99.59	15.64	-7.42
-50	68.97	14.25	-7.16
-45	48.40	12.94	-6.91
-40	34.38	11.69	-6.67
-35	24.71	10.51	-6.45
-30	17.97	9.39	-6.23
-25	13.20	8.33	-6.02
-20	9.804	7.31	-5.82
-15	7.352	6.35	-5.63
-10	5.565	5.43	-5.45
-5	4.251	4.55	-5.28
0	3.275	3.70	-5.11
5	2.544	2.90	-4.95
10	1.992	2.13	-4.80
15	1.572	1.39	-4.65
20	1.249	0.68	-4.51
25	1.000	0.00	-4.38
30	0.8057	0.66	-4.25
35	0.6534	1.30	-4.12
40	0.5331	1.92	-4.00
45	0.4376	2.53	-3.89
50	0.3612	3.12	-3.77
55	0.2998	3.70	-3.67
60	0.2501	4.26	-3.57
65	0.2097	4.81	-3.47
70	0.1767	5.35	-3.37
75	0.1496	5.87	-3.28
80	0.1272	6.38	-3.19
85	0.1087	6.88	-3.11
90	0.0932	7.37	-3.03
95	0.0803	7.84	-2.95
100	0.0694	8.31	-2.87
105	0.0602	8.76	-2.80
110	0.0524	9.21	-2.73
115	0.0458	9.64	-2.66
120	0.0402	10.07	-2.60
125	0.0353	10.48	-2.53
130	0.0312	10.89	-2.47
135	0.0276	11.29	-2.41
140	0.0245	11.68	-2.36
145	0.0218	12.06	-2.30
150	0.0194	12.43	-2.25

B25/50	B25/75	B25/85	B25/100	B Tol
3925 K	3944 K	3950 K	3958 K	$\pm 3\%$

R Min (Ω)	R Nom (Ω)	R Max (Ω)
2,499,839	3,884,018	5,268,197
1,768,659	2,690,002	3,611,346
1,265,731	1,887,409	2,509,087
915,834	1,340,794	1,765,754
669,710	963,820	1,257,930
494,737	700,707	906,676
369,068	514,948	660,828
277,918	382,358	486,799
211,176	286,722	362,268
161,858	217,043	272,229
125,094	165,788	206,481
97,457	127,735	158,013
76,511	99,234	121,957
60,511	77,705	94,900
48,197	61,311	74,425
38,652	48,729	58,806
31,200	39,000	46,800
24,932	31,423	37,914
20,054	25,481	30,908
16,233	20,791	25,349
13,220	17,065	20,909
10,829	14,086	17,343
8,920.2	11,691	14,462
7,387.5	9,754.1	12,121
6,149.9	8,179.4	10,209
5,145.2	6,892.3	8,639.4
4,325.4	5,834.9	7,344.5
3,653.0	4,962.0	6,271.1
3,098.8	4,238.0	5,377.2
2,640.0	3,634.7	4,629.5
2,258.4	3,129.9	4,001.3
1,939.7	2,705.6	3,471.5
1,672.4	2,347.6	3,022.8
1,447.2	2,044.3	2,641.3
1,256.9	1,786.4	2,315.8
1,095.3	1,566.2	2,037.1
957.7	1,377.6	1,797.5
840.1	1,215.5	1,591.0
739.2	1,075.8	1,412.3
652.4	954.8	1,257.3
577.4	849.9	1,122.3
512.5	758.5	1,004.5